

SIMULATOR IN-FLIGHT COCKPIT SETUP

BATT/GEN/AUX BATT.....	On
Avionics Master	On
Probes Anti-Ice.....	On
Bleed Air Inflow.....	Norm
O2.....	Normal
Altimeter.....	29.92
TCAS.....	On
TAD.....	On
Gear/Flaps.....	Up
Friction Lock.....	Adjusted
PCL.....	Set (for 200 KIAS)
Seat and Rudder Pedals	Adjusted
Seat Safety Pin.....	Removed and Stowed

SIMULATOR GROUND PROCEDURES CHECKLIST

Initial cockpit set up: Adjust seat height and rudder pedals;
Batt, Gen, Aux Batt on; Avionics master on; Bleed air inflow
Norm; O2 normal; TAD on; TCAS on

BEFORE TAXI

19. UFCP AND MFD'S

- b. UHF..... Copy ATIS and Obtain Clearance
 - c. VHF COM..... Set as Required
 - d. VOR..... Set as Required
 - e. Transponder..... SET, STANDBY
 - f. FMS and FLT NO..... Set as Required
 - g. Alt, G, Speed, Fuel flags..... Set as Required
21. ALTIMETERS..... SET AND CHECKED TWICE (BOTH)

Call for TAXI

BEFORE TAKEOFF

- 3. FLAPS..... TAKEOFF
- 4. TRIM..... SET for TAKEOFF
- 10. SEAT SAFETY PIN..... REMOVED AND STOWED (BOTH)
- 11. ISS MODE SELECTOR..... BOTH, **ROGER BOTH**

Call for TAKEOFF

LINEUP CHECKLIST

- 1. EXTERIOR LIGHTS ON
- 2. TRANSPONDER ALTITUDE
- 3. PROBES ANTI-ICE SWITCH ON
- 4. NOSE WHEEL STEERING OFF
- 5. EICAS DISPLAY CHECKED (BOTH)

Flight Manual Date: 01 December 2017; Change 1 01 August 2019